



PRODUCT INFORMATION/ /HAZARD ALERT/CARE TIPS

CARPETED FOAM FLOOR ROLLS & FLEXI-ROLLS®

READ THIS DOCUMENT AND ALL OTHER ACCOMPANYING PRODUCT DOCUMENTATION THOROUGHLY BEFORE INSTALLING, USING OR PERMITTING USE OF THIS EQUIPMENT. REQUIRE ALL PERSONS INTENDING TO USE THIS EQUIPMENT, AS WELL AS THOSE INSTRUCTING OR COACHING USERS, ASSISTING USERS AND/OR SPOTTING USERS TO READ THIS DOCUMENT THOROUGHLY BEFORE YOU AUTHORIZE EQUIPMENT TO BE UTILIZED FOR ANY PURPOSE.

1. Keep your Carpeted Foam Floor clean by minimizing direct tracking onto surface.
 - a. Position doormats around floor perimeter and require all users to wipe their feet on those before walking onto floor.
 - b. Do not permit anyone to step on floor while wearing footwear used outside your facility. Requiring all participants to maintain an extra pair of shoes to be used only on your floor is the most effective means of keeping carpet clean.

2. Frequent vacuuming, supplemented by periodic water extraction (“steam cleaning”) is recommended to maintain carpet appearance and hygiene.
 - a. Do not use detergent or soap during water extraction cleaning. Remaining residue will make carpet feel sticky and attract more dirt and grime. (See 3 b, c & d below.)
 - b. Remember foam base does not absorb water like carpet padding.
 - c. Be sure to extract as much water as possible from carpeted floor surface. Place several large fans around floor to accelerate drying.
 - d. Because foam base doesn't absorb water, more water may be used. CAUTION: Water may seep between rolls and damage facility floor underneath your carpeted floor.
 - e. After each water extraction cleaning, roll up floor to inspect and dry building flooring.

3. To sanitize floor carpet:
 - a. Check with building maintenance to determine what they use for sanitizing locker room and training table surfaces.
 - b. Many regional health departments consider a 1 part bleach to 10 parts water solution an effective antibiotic.
 - c. Bleach/water solution may be used in water extraction system. Extra rinse step may be necessary to reduce bleach odor.
 - d. While a 1/10 bleach/water solution will not damage nor discolor floor carpeting, Velcro strips may be adversely affected. Remove Velcro strips prior to bleach cleaning.
 - e. Remember wet bleach will likely damage clothing on contact.

FLEXI-ROLL® is a registered trademark of Dollamur, LP.

RISK OF SERIOUS INJURY, PARALYSIS AND/OR DEATH, IS INHERENT IN ALL ACTIVITIES INVOLVING MOTION OR HEIGHT. THIS EQUIPMENT IS TO BE USED ONLY BY PROPERLY TRAINED, QUALIFIED PERSONS UNDER SUPERVISED CONDITIONS. USE WITHOUT PROPER SUPERVISION IS DANGEROUS AND SHOULD NEVER BE UNDERTAKEN NOR PERMITTED. NORBERT'S ATHLETIC PRODUCTS, INC. SHALL NOT BE LIABLE NOR RESPONSIBLE FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED THROUGH THE USE OR MISUSE OF THIS EQUIPMENT OR ANY OTHER PRODUCT MANUFACTURED BY NORBERT'S ATHLETIC PRODUCTS, INC.