

WALL PADS

READ THIS DOCUMENT AND ALL OTHER ACCOMPANYING PRODUCT DOCUMENTATION THOROUGHLY BEFORE INSTALLING, USING OR PERMITTING USE OF THIS EQUIPMENT. REQUIRE ALL PERSONS INTENDING TO USE THIS EQUIPMENT, AS WELL AS THOSE INSTRUCTING, ASSISTING OR COACHING OTHERS IN THE USE OF THIS PRODUCT, TO READ THIS DOCUMENT THOROUGHLY BEFORE AUTHORIZING THEM TO ENGAGE IN THOSE OR RELATED ACTIVITIES.

DESCRIPTION

Norbert's Wall Pads are mounted on interior walls to provide cushioned impact attenuation surfaces. All consist of rigid 1/2" thick OSB oriented strand board backing, 18oz coated vinyl fabric covering and foam filler. Filler foam is bonded to backing. Vinyl cover is wrapped around foam front and side surfaces of pad, then stapled to backing.

Vinyl cover material is available in these colors: Royal Blue, Red, Green, Orange, Yellow, White, Black, Light Blur, Maroon, Dark Green, Lime Green, Pink, Purple, Grey and Tan.

Two styles--differentiated by foam filler type--are offered.

DIMENSIONS:

Standard Wall Pad width is 24". Four standard heights are offered: 48", 60", 72", and 84". Custom sizes/shapes--to maximum width of 48" x maximum height of 96"--are available as are cut-outs permitting access to power switches, boxes, panels, etc.

STYLE 1 WALL PADS

DESCRIPTION:

STYLE 1 WALL PADS are filled with 1-3/8" thick crosslinked polyethylene.

MATERIALS

- BACKING: 1/2" thick OSB (oriented strand board).
- FILLER FOAM: 1-3/8" thick Crosslinked Polyethylene with a density rating of 2.0 lbs pcf. Complies with Federal Motor Vehicle Safety Standard (FMVSS) 302 for fire retardancy and ASTM F2440-04 requirements for indoor wall pads.
- VINYL COVER FABRIC: 18 oz coated vinyl fabric (1000 denier polyester scrim) with a tensile strength of 270x270 lbs/inch and tear strength of 100x90 lbs. Material complies with minimum flame resistance requirements as specified in CHSC Section 13115 and is so certified by the California Fire Marshall (Reg# FA-48006). Material is also UV protected as well as mildew/rot/fungus resistant.

STYLE 2 WALL PADS

DESCRIPTION:

STYLE 2 WALL PADS are filled with 2" thick 200 ILD prime polyurethane.

MATERIALS

- BACKING: 1/2" thick OSB (oriented strand board).
- FILLER FOAM: 2" thick 200 ILD prime polyurethane.
- VINYL COVER FABRIC: 18 oz coated vinyl fabric (1000 denier polyester scrim) with a tensile strength of 270x270 lbs/inch and tear strength of 100x90 lbs. Material complies with minimum flame resistance requirements as specified in CHSC Section 13115 and is so certified by the California Fire Marshall (Reg# FA-48006). Material is also UV protected as well as mildew/rot/fungus resistant.

IMPORTANT CONSUMER PRODUCT HAZARD WARNING — PLEASE READ!

A possibility of serious injury, including paralysis or death, is inherent in any activity involving motion or height. Equipment with which this notice is included is intended for use only by properly trained, qualified persons under supervised conditions. Use without proper supervision is dangerous and should not be undertaken or permitted. Know your limitations as well as the limitations of your equipment. Consult a qualified instructor before attempting any new activity or skill. This equipment must be used with proper mats, spotting equipment and qualified spotters for each activity or skill. Use this equipment only for its intended purpose. Do not modify equipment in any way. Inspect each component for damage, loose fittings or signs of wear before each use. Do not use if you have any concern as to the condition of this equipment. Test unit for stability prior to each use. Do not use if you have any concern about the stability, condition or suitability of this equipment. Inspect warning labels and replace when marred or damaged. Before each subsequent use, re-check equipment stability and settings.